## RADIAL DRILLING MACHINES - AMT MODEL 40MM BELT DRIVEN



40 mm cap. Backgeared Autofeed Radial Drill Machine

Exclusive Features of R40BA series



- Oil Bath lifting assembly.
- Steel worm supported through ball bearings at both sides.
- Screw supported through taper roller bearings.



- Wide supports of column, column bracket & arm.
- Heavy duty lifting screw of 35 mm die.




- Long bottom for greater rigidity to reduce vibration.
- Heavy duty column with Heavily ribbed base plate.



- 250 mm long spindle travel.
- 78 mm Steel RAM with 2.5 Module Heavy Teeth.



Greater support through closed V - Guideways and wider drilling ▶ head.



Better design of arm for higher rigidity and wide support.

## **SPECIFICATIONS**

DESCRIPTION	R40BA
Drilling in M.S.	40
Drilling in C.I.	45
Tapping in M.S.	20
Rough Boring in M.S.	75
Spindle Taper	MT-4
Spindle Travel	250
Spindle Speeds (RPM x steps)	88-2600 x 8
Diameter of RAM	78
Spindle Autofeed Ranges	0.05 & 0.09
Max/Min Dist. Spindle nose to base	850/250
Max/Min Dint. Spindle center to column	920/385
Max. Drilling Radius	1005
Machine Measurement (LX B X H)	1350 x 850 x 1825
Diameter of Column	170
Work Table	300 x 300 x 385
Drill-head Motor	1.5 HP/1440 RPM
Elevating Motor	1 HP/1440 RPM
Head Motor V-belt	B-47
Lifting Motor V-belt	B-25/B-26

## STANDARD ACCESSORIES

## **OPTIONAL ACCESSORIES**



B - 73, PHASE - 1, MAYAPURI INDUSTRIAL AREA (BEHIND POLICE STATION), NEW DELHI - 110 064, INDIA MOBILE : +91-9810112341, PHONE : +91-11-28117865, +91-11-30583633, FAX : +91-11-28117867

Email : <u>iimc@vsnl.net</u>, <u>iimc.machines@gmail.com</u>
Website : <u>www.iimc-india.com</u>, <u>www.indiamart.com/indiainternational</u>